

MODEL	SHAFT SIZE	GAUGE	HEIGHT	BASE	ANCHORAGE
RNTS Round Non Tapered Steel	4R 4"Ø	11	10'	9BC 9" Base 9 3/16" BC	343 3/4" X 30"
			12'		
			14'		
			16'		
			18'		
			20'		
		11	22'	12BC	136
	4R 4"Ø	7	25'	12" Base	1" X 36"
			28' *7G Only	12 3/4" BC	
		11	20'	12BC	136
	5R 5"Ø	7	22'	12" Base	1" X 36"
			25'	12 3/4" BC	
			28'		
			30'		
			35' *7G Only		
		7	28'	12BC	136
	6R 6"Ø	7	30'	12" Base	1" X 36"
			35'	12 3/4" BC	

CBC
Custom Bolt Circle
• Consult Factory

Direct Burial
* Consult Factory

MOUNTING	FINISH	OPTIONS
----------	--------	---------

S1
Single Bolt-On Arm



D2
Double 180° Bolt-On Arm



D9
Double 90° Bolt-On Arm



T1
Triple 120° Bolt-On Arm



T9
Triple 90° Bolt-On Arm



QD
Quad Bolt-On Arm



Tenon Options

T238R
2 3/8"

T3R
3"

T3.5R
3 1/2"

T4R
4"

BZ
Bronze

BK
Black

SBK
Smooth Black

WH
White

SWH
Smooth White

GP
Graphite

GY
Grey

SL
Silver Metallic

GN
Tennis Green

FG
Forest Green

CC
Custom Color

WGF
Custom Wood Grain Finish
*20' Max Pole Height
* Consult Factory

GAL
Galvanized
*No Paint
* Consult Factory

XX+GAL
Powder Coat Paint Over Galvanized
* Consult Factory

ZRP
Zinc-Rich Primer Coat
* Consult Factory

GFI

GFI Receptacle
*Standard location is in hand hole.
*Specify GFI location if different from hand hole location.
Supplied with in use cover.

USB

USB Receptacle
*Specify location. Supplied with in use cover.

CUP1/2

Coupling 1/2"
*Specify location

CUP3/4

Coupling 3/4"
*Specify location

HCR

Rust-Inhibiting Internal Coating & Primer
*Required for Direct Burial Poles

IVD

Internal Vibration Dampener

RBC

Round Base Cover
*Consult Factory

EB

Eye Bolt

UL

UL Certified